



universal sling

One of the most popular full body slings, providing safe, supportive and easy transfers. Its split leg design offers high levels of support and ease of toileting. The range provides options for various fabrics to ensure the sling fits perfectly to each individual, whether they have some mobility impairment or require full body and head support.

An easy to fit and very supportive full body sling which can be used in a divided leg or cross over position. It provides the person with a feeling of comfort and safety as well as an unobstructed view to help them assist in their own transfer. This sling is suitable for those with good head control.



Materials

Made from highly durable polyester, this sling is easy to apply and is compatible with all hoists that use hook and loop spreader bar systems e.g. the Smirthwaite 130 Mobile Hoist or the Smirthwaite CP130.

The spacer material has been designed to provide added comfort to the user as the stretchy material can fit around the individual. This sling is suitable for those who wear slings for extended periods.

Colours



Size	Colour	Code
Junior	Black Spacer	3501
Child	Black Spacer	3502
Junior	Pink Spacer	3503
Child	Pink Spacer	3504
Junior	Aqua Blue Spacer	3505
Child	Aqua Blue Spacer	3506

Features & Benefits

- Full body support for those who have good head control
- Versatile, durable and robust
- Suitable for transfers to and from a sitting position
- Side straps even weight distribution making the sling more comfortable
- Quilted leg sections and no binding on outer leg section provide additional comfort
- Spacer material available
- 1 year warranty

Technical Specification

all dimensions in mm unless otherwise stated

Size	A	B	C	D	E
Junior	750	940	490	450	750
Child	610	770	390	380	610

All slings are available with or without head support. All dimensions have a tolerance of +/- 20mm.

These slings include colour coded bindings around the edge of the sling to help identify the sling size. Sling sizes are in accordance with the maximum weight capacity as indicated in the table below.